

### LTC Levellogger Junior Level, Temperature, Conductivity

The LTC Levellogger Junior logs conductivity, as well as water level and temperature. Like the LT Levellogger Junior, it is easy to transport, program, deploy and retrieve data. It combines a datalogger, 5-year battery, pressure transducer, and temperature and conductivity sensors within a small waterproof housing, 7/8" x 7.5" (22 mm x 190 mm).

The conductivity sensor is a 4-electrode platinum sensor, with auto-ranging capabilities. The minimal maintenance, sealed LTC Levellogger Junior is simple to clean and calibrate, even in the field.

Using standard Levellogger Software, it displays conductivity, temperature, and temperature-compensated water level. Memory is non-volatile and stores up to 16,000 sets of readings. Measurements are linear, in any interval between 5 seconds and 99 hours.

See the Model 3001 Gold Data Sheet for more information on the Levellogger Series of dataloggers, accessories and software.



### Features

- Low Cost
- Three measurements in one probe
- Compatible with Levellogger Software and accessories
- Single or multi-point calibration
- Compact, low maintenance, waterproof design
- Faraday Cage protection against power surges
- Real-time viewing and data export to other programs
- Compatible with Solinst Telemetry Systems and SDI-12

### User-Friendly Operation

Barometric Compensation and Calibration Wizards guide you through the calibration process and compensation, to provide corrected data. Levellogger Software allows you to easily program your preferences, download data, and display data in a graph or table format or export to other programs. Temperature compensation is automatic, but temperature variations can also be displayed.

The Real-Time View option allows immediate viewing of live conductivity, water level and temperature readings. Levelloggers are easy to deploy; installation can be with direct read cables or wireline/rope suspension, avoiding the use of vented cables. (See Model 3001 Gold Data Sheet).

The LTC Levellogger Junior is SDI-12 compatible, can communicate with a Leveloader Gold data transfer device, and is able to integrate into a Solinst Telemetry System. (See Model 9100 and 9200 data sheet).

### Applications

- Salt water intrusion and soil salination monitoring
- Plume remediation monitoring and studies
- Leachate monitoring at landfills, mine tailings, waste disposal storage sites, and more
- Agricultural and stormwater runoff monitoring
- Tracer tests

Technical Specifications	
<b>Level Sensor:</b>	Piezoresistive Silicon in 316L SS
Ranges:	F30/M10, F100/M30
Accuracy (typical):	0.1% FS
Resolution:	0.08" (0.2 cm), 0.24" (0.6 cm)
Normalization:	Automatic Temp Compensation
<b>Temperature Sensor:</b>	Platinum RTD
Accuracy:	± 0.1°C
Resolution:	0.1°C
Temp Compensation Range:	-10°C to 40°C
<b>Conductivity Sensor:</b>	4-Electrode Platinum
Full Range:	0 - 80,000 µS/cm
Calibrated Range:	500 - 50,000 µS/cm
Accuracy:	2% of reading or 20 µS/cm
Resolution:	1 µS
Temp. Compensation Range:	0°C to 40°C
Normalization:	Specific Conductance @ 25°C
<b>General:</b>	
Battery Life:	5 Years (5 minute sampling rate)
Clock Accuracy:	± 1 minute/year from 0 to 40°C
Operating Temperature:	- 20°C to 80°C
Memory:	Non-volatile EEPROM, FRAM back-up
Maximum Readings:	16,000 sets of readings
Communication:	Optical Infra-Red to USB or RS232
Size:	7/8" x 7.5" (22 mm x 190 mm)
Weight:	7.05 oz. (200 grams)
Wetted Materials:	Platinum, 316 Stainless Steel, Delrin®, Viton®
Sampling Mode:	Linear, (5 sec to 99 hrs) SDI-12, Real Time View
Barometric Compensation:	Software Wizard and Barologger Gold



WEEE ®Solinst is a registered trademark of Solinst Canada Ltd.

® Delrin and Viton are registered trademarks of DuPont Corp.

Printed in Canada  
July 27, 2010

**For further information contact: Solinst Canada Ltd.**  
 Fax: +1 (905) 873-1992; (800) 516-9081 Tel: +1 (905) 873-2255; (800) 661-2023  
 35 Todd Road, Georgetown, Ontario Canada L7G 4R8  
 Web Site: [www.solinst.com](http://www.solinst.com) E-mail: [instruments@solinst.com](mailto:instruments@solinst.com)

# Solinst®